



Unmanaged Media Converter Chassis

The 2U 14 slots Rack Mount Media Converter Chassis provides higher rack mount media converter density for large installations that can accommodate rear access to the chassis for power supply maintenance. The 14 slots media converter chassis supports plug-and-play installation of stand-alone media converters convert modules, can hold at most 14 pieces media converters.

The High port density allows a variety of media converter solutions to be housed in a minimum amount of rack spaces for enterprise-level businesses and carriers. Redundant, fan-cooled load-sharing power supplies can be hot-swapped to ensure system uptime.

Features

- Cross flow cooling fan built-in
 - Number of slots: 14
 - 14 slots chassis: 10/100M or 10/100/1000M stand-alone external power supply media converters
 - Easy maintenance
 - Meets the requirement of good stability, high capacity, good integration and good quality
-

Applications

- FTTx
- Telecommunication networks
- LAN

Specifications

| DESCRIPTION | |
|-----------------------------|---|
| Number of slots: | 14 |
| Media converters adapted: | 14 slots chassis: 10/100M or 1000M or 10/100/1000M stand-alone media converters |
| Power in: | AC 100V~260V; OR DC 48V |
| Power out: | DC 5V, 12A |
| Diameter of DC plug: | 2.5/5.5 mm |
| Ripple: | ≤50 Mv |
| Noise: | ≤50 Mv |
| Protection of power supply: | Circuit-breaker when overvoltage; circuit-breaker when overflow; circuit-breaker when short circuit |
| Operating Temperature: | 0°C~50°C |
| Storage Temperature: | -20°C ~85°C |
| Humidity: | 5%~95% |
| Dimensions: | 485mm x231mm x 90mm (LxWxH) 19 inches 2U |

Ordering Information

| DESCRIPTION | PART NUMBER |
|---|-------------|
| OptronicsPlus 2U 14 Slots Media Converter Chassis | OMCC-14-2U |