



Category 6 U/UTP - Unshielded Twisted Pair Dca LSZH Cable

The Category 6 Unshielded Twisted Pair (U/UTP) Dca LSZH cable with 4 x 2 x 23 AWG copper wire structure fully complies with ISO/IEC 11801 and TIA/EIA 568 standards. They ensure optimum bandwidth for today's high speed network applications and are designed to deliver a robust standard based performance. OptronicsPlus Cat6 U/UTP cable exceeds Cat6/Class E performance requirements and supports 10-BASE-T, 100-BASE-TX and 1000Base-T applications. The Dca LSZH sheath offers excellent fire performance making this the ideal choice in public buildings and other high-risk locations.

Features

- 23 AWG conductors
- Exceeds Cat6 performance requirements
- ISO/IEC 11801 and TIA/EIA568 compliant
- Reaction-to-fire class according to EN 13501-6: Dca
- Available with flame retardant LSZH outer jacket
- Supplied in 305m boxes or 500m reels
- Printed metre marks

Applications

- Cat6/Class E up to 250Mhz applications
- 10BASE-T, 100BASE-TX, 1000Base-T applications
- Horizontal network installations
- Backwards compatible with Category 5e distribution systems

Specifications

CONSTRUCTION

Conductor	23AWG (0.550 ± 0.01mm) Solid bare Copper
Insulation	Polyethylene (HDPE)
Cable	8 insulated wires formed into 4 pairs.
Sheath	LSZH-Dca
Test Method	EN 50575
Euro Class	Dca-s1a,d1,a2
Halogen free (acc. EN 60754-1/2)	Yes
Flame retardant	In accordance with EN 60332-1-2 and EN 50399
Average Thickness	0.60mm ± 0.1
Diameter	6.8mm ± 0.35

Electrical properties at 20 °C

Characteristic Impedance (1-100MHz)	100 ± 15Ω
DC loop resistance	≤ 19.0Ω/100m
Resistance unbalance	≤ 2%
Capacitance unbalance to earth	≤ 1600pF/km
Delay Skew	≤ 40ns/100m @ 100MHz
Nominal velocity of propagation	67%
Propagation delay (Nominal)	≤ 534ns/100m
Test voltage (d.c. for 1 minute) Conductor/Conductor	1000V
Insulation resistance (500V d.c.)	≥ 500MΩ.km
Coupling attenuation	≥ 40dB
Temperature Rating	-20°C— + 70°C
Cold Bend (-20±2°C×4)	8×Cable O.D. No visible cracks

Mechanical Characteristics Temperature Range

Operation	-20°C to + 60°C
Installation	0°C to + 50°C
Storage	-20°C to + 70°C

Maximum Tensile Force

During Installation	100N
---------------------	------

Minimum Bend Radius

Installation	8 x Cable Diameter
Installed	8 x Cable Diameter

Transmission Line Performance

FREQUENCY (MHz)	ATTENUATION DB/100M	NEXT DB	ACR DB	MIN DB PSNEXT	MIN DB ELFEXT	MIN DB PSELFEXT	MIN DB RETURN LOSS
1	2.1	74.0	71.9	72.0	68	65	20
4	3.8	65.3	61.5	63.3	56	53	23
10	6.0	59.3	53.3	57.3	48	45	25
16	7.6	56.0	48.4	54.0	44	41	25
20	9.3	45.8	36.5	42.8	42	39	25
62.5	17	38.4	21.4	35.4	32	29	21.5
100	22.0	35.3	13.3	32.3	28	25	20.1
125	22.5	43.0	20.5	41.0	26	23	19.5
155.5	25.4	42.0	16.6	40.0	24	21	18.8
250	33.0	38.3	5.3	32.3	20	17	17.3

Standards Compliance

The CAT6 U/UTP Dca LSZH cable is manufactured and tested directly in accordance with the major industry standards:

- Class E / Category 6
- ANSI/TIA/EIA-568-C.2
- ISO/IEC 11801 2nd Edition
- EN 50173
- IEC 61156-5
- EN 50288-3-1
- IEC 60332-1-2
- IEC 60754-2
- IEC 61034
- EN 50575
- RoHS / REACH / SvHC

Ordering Information

DESCRIPTION	PART NUMBER
CAT6 U/UTP 23 AWG Dca LSZH Cable - 305m box	OCC-6-11-305-DCA
CAT6 U/UTP 23 AWG Dca LSZH Cable - 500m reel	OCC-6-11-500-DCA

Additional Images

