



Secondary Coated 900um Fibre

900µm secondary coated multimode (OM1/OM2/OM3/OM4) or singlemode (G.652.D) pigtail cable. It's available in standard or easy strip format and in 12 standard colours.

Features

- 900µm secondary coated fibre
- Choice of buffering material and stripping options
- Available in various fibre types
- Available also in 12 standard colors with white as the standard colour

Applications

- Pigtails
- Ideal for cable termination in patch panels, ODFs and wall boxes

Specifications

DESCRIPTION		1-CORE
Outer Diameter	mm	0.9
Weight	kg/km	0.9
Max. Load (installation)	N	6
Max. Load (installed)	N	3
Min. bend radius (installation)	mm	30
Min. bend radius (installed)	mm	30
Temperature Range	°C	-20 ~+70

Ordering Information

	Colour	Fibre Type	Jacket Type	Jacket Type	Extra Options					
OFC-PT	1	White	9	G.652.D	1	LSZH	01	1		Tight Buffered
	2	Yellow	1	OM1					E	Easy Strip
	3	Pink	2	OM2						
	4	Green								
	5	Red								
	6	Orange								
	7	Grey								
	8	Purple								
	9	Aqua								
	10	Black								
	11	Brown								
	12	Blue								

Example order code

OFC-PT	-	1	9	1	-	01
--------	---	---	---	---	---	----

Secondary Coated 900um Tight Buffered Fibre Cable Singlemode LSZH White 1 Fibre